

Specifications

	SPR-7116	SPR-7416
Main Spec.	CPU : Intel P-VI 2.8GHz SDRAM 512MB VGA : ATI VGA 128MB LAN : 10 / 100 MB Built-in CD-RW Drive O/S : Windows 2000 Professional	CPU : Intel P-VI 2.8GHz SDRAM 512MB VGA : ATI VGA 128MB LAN : 10 / 100 MB Built-in CD-RW Drive O/S : Windows 2000 Professional
Video Input	16CH Composite Video(NTSC/PAL)	16CH Composite Video(NTSC/PAL)
Video Output	RGB(PC) : 1CH, Composite(Normal Monitor) : 1CH	RGB(PC) : 1CH, Composite(Normal Monitor) : 1CH
Recording resolution mode	160x120, 320x240, 640x240, 640x480 (NTSC)	160x120, 320x240, 640x240, 640x480 (NTSC)
Recording speed(Frame/sec)	Max. 120/100 ips(NTSC/PAL)	Max. 480/400 ips(NTSC/PAL)
Compression Method	Modified H.263	Modified H.263
Compression rate	Average 2.5KB/Frame (320x240: NTSC / 352x288: PAL standard resolution)	Average 2.5KB/Frame (320x240: NTSC / 352x288: PAL standard resolution)
Watermark	Able to check the authentication of the restored image	Able to check the authentication of the restored image
Audio Recording	1CH	1CH
Display mode & Number of	1, 4, 9, 16 split screen, full screen, 16CH real time monitoring 480/400 ips (NTSC/PAL)	1, 4, 9, 16 split screen, full screen, 16CH real time monitoring 480/400 ips (NTSC/PAL)
Frame	1 ~ 10 seconds	1 ~ 10 seconds
Auto switching	Simultaneously playback each channel from 4,9,16 split screen.	Simultaneously playback each channel from 4,9,16 split screen.
Playback display mode	16CH : NO(Normal Open Type) or NC(Normal Close Type)	16CH : NO(Normal Open Type) or NC(Normal Close Type)
Sensor Input	Output through 16CH of NO/NC	Output through 16CH of NO/NC
Alarm Output	Selectable detection sensitivity and area	Selectable detection sensitivity and area
Motion Detection	M : N operation	M : N operation
Camera/Sensor	Pan/Tilt/Zoom Camera control through RS-422 connection	Pan/Tilt/Zoom Camera control through RS-422 connection
Pan/Tilt/Zoom Control	LAN : 120 Frames/sec(Max), ISDN : 3~10 Frames/sec, PTSN : 1 ~ 5	LAN : 120 Frames/sec(Max), ISDN : 3~10 Frames/sec, PTSN : 1 ~ 5
Transmission speed	Frames/sec	Frames/sec
Data backup	Auto/Manual back up through HDD, CD-RW, DVD, Network Drive	Auto/Manual back up through HDD, CD-RW, DVD, Network Drive
Power requirements	AC100~240V, 5Amax, 60Hz	AC100~240V, 5Amax, 60Hz
Weight	Approx.18Kg	Approx.18Kg
Dimensions	431(W)x177(H)x459(D)	431(W)x177(H)x459(D)

* "P" indicates PAL model & "N" or no specific alphabet after the model name indicates NTSC model.